

THIRD ORDER SUSCEPTIBILITY OF PLATINUM SULFIDE SOL

by

**Dr. Kenneth LaiHing
Dept. of Chemistry
Oakwood College
Huntsville, AL 35896**

for

**U.S. Army Missile Command
Felicia L. Hereford-Kaigler
Redstone Arsenal
Huntsville, AL 35896-5254**

December 28, 1992

Contract # DAH01-92-P-R021

DISTRIBUTION STATEMENT A

**Approved for public release;
Distribution Unlimited**

19980223 158

DTIC QUALITY INSPECTED 3

10
"Third order of susceptibility of Platinum Sulfide Sol"

PLEASE CHECK THE APPROPRIATE BLOCK BELOW:

AO # 1196-04-0345

☐ 1 copies are being forwarded. Indicate whether Statement A, B, C, D, E, F, or X applies.

☒ **DISTRIBUTION STATEMENT A:**
APPROVED FOR PUBLIC RELEASE: DISTRIBUTION IS UNLIMITED

☐ **DISTRIBUTION STATEMENT B:**
DISTRIBUTION AUTHORIZED TO U.S. GOVERNMENT AGENCIES ONLY; (Indicate Reason and Date). OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO (Indicate Controlling DoD Office).

☐ **DISTRIBUTION STATEMENT C:**
DISTRIBUTION AUTHORIZED TO U.S. GOVERNMENT AGENCIES AND THEIR CONTRACTORS; (Indicate Reason and Date). OTHER REQUESTS FOR THIS DOCUMENT SHALL BE REFERRED TO (Indicate Controlling DoD Office).

☐ **DISTRIBUTION STATEMENT D:**
DISTRIBUTION AUTHORIZED TO DoD AND U.S. DoD CONTRACTORS ONLY; (Indicate Reason and Date). OTHER REQUESTS SHALL BE REFERRED TO (Indicate Controlling DoD Office).

☐ **DISTRIBUTION STATEMENT E:**
DISTRIBUTION AUTHORIZED TO DoD COMPONENTS ONLY; (Indicate Reason and Date). OTHER REQUESTS SHALL BE REFERRED TO (Indicate Controlling DoD Office).

☐ **DISTRIBUTION STATEMENT F:**
FURTHER DISSEMINATION ONLY AS DIRECTED BY (Indicate Controlling DoD Office and Date) or HIGHER DoD AUTHORITY.

☐ **DISTRIBUTION STATEMENT X:**
DISTRIBUTION AUTHORIZED TO U.S. GOVERNMENT AGENCIES AND PRIVATE INDIVIDUALS OR ENTERPRISES ELIGIBLE TO OBTAIN EXPORT-CONTROLLED TECHNICAL DATA IN ACCORDANCE WITH DoD DIRECTIVE 5230.25. WITHHOLDING OF UNCLASSIFIED TECHNICAL DATA FROM PUBLIC DISCLOSURE. 6 Nov 1984 (Indicate date of determination). CONTROLLING DoD OFFICE IS (Indicate Controlling DoD Office).

☐ This document was previously forwarded to DTIC on _____ (date) and the AD number is _____.

☐ In accordance with provisions of DoD instructions, the document requested is not supplied because:

☐ It will be published at a later date. (Enter approximate date, if known).

☐ Other. (Give Reason)

DoD Directive 5230.24, "Distribution Statements on Technical Documents," 18 Mar 87, contains seven distribution statements, as described briefly above. Technical Documents must be assigned distribution statements.

25AR MC / Redstone
Jim Mayfield
Print or Type Name
Per: Dr. K. Lai King
DSN 746-5181
Telephone Number

gc
Jose J. Chirias
Authorized Signature/Date

Third Order Susceptibility of Platinum Sulfide Sols

The optical properties of a suspension of small metal particles in a transparent medium can differ strikingly from those of the same metal in bulk form. New materials with large values of χ^3 , the third order nonlinear susceptibility tensor are needed. Recent trends in nonlinear optics have centered on processes involving χ^3 . One method of determining χ^3 involves the measurement of the optical phase conjugate signal generated by the sample. Experimentally this is determined using degenerate four-wave mixing (DFWM). Pure sulfur sol was prepared by dissolving the solid sulfur in hydrazine, followed by addition of distilled water with vigorous stirring. The sulfur sol thus produced was sealed and stored in the dark.

Platinum sols were produced by reduction of platinum chloride with 1% sodium citrate. Both solutions were mixed and heated for 30 minutes at 80 °C. Finally, both the sulfur sol and platinum sol were mixed in equal parts and heated while stirring at 80 °C for approximately 15 minutes until no further color change.

UV-Visible spectra were taken of the final platinum sulfide sol. This is shown in Figure 1. The final concentration of the platinum sulfide sol was 1.64×10^{-3} M.

The phase conjugate signal intensity was measured using DFWM. The experimental arrangement used for DFWM is shown schematically




FIGURE 1.




FIGURE 1A.




FIGURE 2. Experimental Arrangement for Degenerate Four-Wave Mixing

in Figure 2. Briefly it consisted of a lens A which focuses the beam on the sample. The optical density filter B was used to vary the intensity of all three beams. Beam splitters BS1 (5%T) and BS2 (50%T) were used to generate the probe, front pump and back pump beams respectively. All beams arrive at the sample simultaneously. The beamsplitter BS3 is used to pick off the conjugate signal which is then focused on a photodiode detector and the signal displayed on a Tektronix 2465 300MHz oscilloscope. The beam intensity was measured by another detector placed between the sample and the back pump beam and displayed on another Tektronix oscilloscope.

The intensity of the phase conjugate signal was determined from the log-log plot of the phase conjugate signal intensity versus the laser power. A similar plot was made for the reference material carbon disulfide at the same wavelength of 480nm.

The value of X^3 for platinum sulfide was 9.11×10^{-13} esu.